



KMD300

300 Series carbon monoxide (CO) detector and base

Application

The KMD300 detector is designed as a carbon monoxide detector for the KM300 CO detection systems. The KMD300 is an intelligent device that delivers its carbon monoxide reading to the control panel for visualization via a 3-wire bus system.



Details

- Complies with UNE 23300:1984, CE, WEEE, RoHS
- Microprocessor based, SMT technology
- Electrochemical CO sensor with high gas discrimination
- Resolution of up to 1 ppm, less than 5% error in measurement
- Fast response time
- No calibration required
- Low current consumption
- BI-Colour diagnostic LED
- Supported by KM300 CO panels
- Useful life of 5 years
- Number of detectors per zone

KMD300

300 Series carbon monoxide (CO) detector and base

Technical specifications

Electrical

Operating voltage	10 to 20 VDC (supply voltage)
Current consumption	6 mA (quiescent current) 15 mA (alarm current)

Detection

Detection principle	Electrochemical
Coverage area	300 m ² max.
Range	0 to 300 ppm

Physical

Physical dimensions	124 x 62 mm (Ø x H, including base)
Net weight	0.3 kg

Environmental

Operating temperature	-10 to +40°C
Storage temperature	-10 to +70°C
Relative humidity	10 to 95%
IP rating	IP42

Compatible products

Category	Reference	Description
Detection device	KZD705	Kilsen KC700 / KA700 / KM300 series deep point detector base
Panel	KM301	Carbon Monoxide Control Panel for Car Parks - 1 Zone
Panel	KM302	Carbon Monoxide Control Panel for Car Parks - 2 Zones
Panel	KM303	Carbon Monoxide Control Panel for Car Parks - 3 Zones
Panel	KM304	Carbon Monoxide Control Panel for Car Parks - 4 Zones