

Audiovisuals / Digital Signage

SF-32DS60

Professional Digital Signage Monitors

Professional digital signage monitors

Digital signage is an advertising format based on the broadcasting of digital content such as images, videos, web content, etc. on multiple devices, including monitors. Generally, these monitors are located at the point of sale or in key locations, being able to create, manage, distribute and publish such content.

- Monitor SAFIRE ELED 32" FHD
- Resolución 1920x1080p
- Software de cartelería digital local
- Entrada HDMI, USB, RS232, RJ-45
- Ángulo de visión de 178°
- Altavoces integrados



Technical Specification

Information	- Android intelligent commercial display screen equipped with messaging - Compatible with horizontal and vertical screen installation
Texture of material	Support ul94-hb75 fire rating
Installation	Support VESA 150x200mm (horizontal and vertical)
Inch	32"
Panel type	VA
Display resolution	1920 x 1080p (FHD)
Brightness	500 cd/m ²
Contrast	4000:1
Viewing angle	178° (H) 178° (V)
Response time	8 ms
Display scale	16:9
Panel life	>= 50000 h
Hard coating	3H
Colour gamut	>= NTSC 85%
Backlight	Side entry backlight (ELED)
Working time	24/7
CPU	T963
RAM	2 GB
ROM	8 GB
OS	Android 9.0
WiFi	2.4 GHz / 5 GHz 802.11a/b/g/n/ac
RTC	Support continuous power-off clock for no less than 7 days and the overall working life is no less
USB 2.0	x2
HDMI 2.0	x3
Line OUT	x1 (3.5mm)
RJ45	x1 (100/10 Mbps)
RS232	x1
Input power	100-240 V @ 50 / 60 Hz
Power interface	1.5 m pluggable power cord
Monitor size	724.6 (W) x 419.8 (H) x 40 (D) mm

Net weight	5.4 kg
Speaker	2 x 10 W
Rated power	70 W
Standby power	0.5 W
Work enviroment	Temperature: 10°C - 40°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa
Storage enviroment	Temperature: 20°C - 55°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa