

Audiovisuals / Digital Signage

# SF-65DS60

## Professional Digital Signage Monitors

### Professional digital signage monitors

Digital signage is an advertising format based on the broadcasting of digital content such as images, videos, web content, etc. on multiple devices, including monitors. Generally, these monitors are located at the point of sale or in key locations, being able to create, manage, distribute and publish such content.

- Monitor SAFIRE ELED 65" 4K
- Resolución 3840x2160
- Software de cartelería digital local
- Entrada HDMI, USB, RS232, RJ-45
- Ángulo de visión de 178°
- Altavoces integrados



## Technical Specification

<b>Information</b>	- Android intelligent commercial display screen equipped with messaging - Compatible with horizontal and vertical screen installation
<b>Texture of material</b>	Support ul94-hb75 fire rating
<b>Installation</b>	Support VESA 400x400mm (horizontal and vertical)
<b>Inch</b>	65"
<b>Panel type</b>	VA
<b>Display resolution</b>	3840 x 2160p (4K)
<b>Brightness</b>	500 cd/m <sup>2</sup>
<b>Contrast</b>	4000:1
<b>Viewing angle</b>	178° (H) 178° (V)
<b>Response time</b>	8 ms
<b>Display scale</b>	16:9
<b>Panel life</b>	>= 50000 h
<b>Hard coating</b>	3H
<b>Colour gamut</b>	>= NTSC 85%
<b>Backlight</b>	Side entry backlight (ELED)
<b>Working time</b>	24/7
<b>CPU</b>	T963
<b>RAM</b>	2 GB
<b>ROM</b>	8 GB
<b>OS</b>	Android 9.0
<b>WiFi</b>	2.4 GHz / 5 GHz 802.11a/b/g/n/ac
<b>RTC</b>	Support continuous power-off clock for no less than 7 days and the overall working life is no less
<b>USB 2.0</b>	x2
<b>HDMI 2.0</b>	x3
<b>Line OUT</b>	x1 (3.5mm)
<b>RJ45</b>	x1 (100/10 Mbps)
<b>RS232</b>	x1
<b>Input power</b>	100-240 V @ 50 / 60 Hz
<b>Power interface</b>	1.5 m pluggable power cord
<b>Monitor size</b>	1459.2 (W) x 837.1 (H) x 38.9 (D) mm

<b>Net weight</b>	25.3 kg
<b>Speaker</b>	2 x 10 W
<b>Rated power</b>	150 W
<b>Standby power</b>	0.5 W
<b>Work enviroment</b>	Temperature: 10°C - 40°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa
<b>Storage enviroment</b>	Temperature: 20°C - 55°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa