

Access Controls / Standalone

SF-AC3003KEMD-IP

Access Control device

Standalone Access Control

Standalone devices with RFID card and fingerprint identification provide quality access control with high adaptability to multiple scenarios and offer ideal storage capacity for the full functionality of the integrated controller.

- Access & Attendance Control Device__
- Identification Fingerprint, EM Card, Keyboard
- Commnication TCP/IP, USB, RS485
- 2,4'' TFT Color Screen
- Custom Status Breaks
- Integrated controller (Door sensor, Push button & Relay)
- Indoor Installation



Technical Specification

Size	2.4-inch
Type	LCD-TFT display screen
Wired network	TCP/IP, 10/100Mbps, self-adaptive
Network interface	1
Lock output	1
Exit button	1
Door contact input	1
Card type	EM card
Fingerprint module	Yes
Fingerprint comparing mode	1:1 and 1:N
Keypad	Keypad with 10 Keys (0 to 9)
Working temperature	-10 °C to +55 °C (14 °F to +131 °F)
Working humidity	10% to 90% (no condensing)
Color	Silver
Dimensions	140 mm × 155 mm × 30 mm (5.51" × 6.01" × 1.18")
Self Service Reports (SSR)	Stand-alone operation, calculate attendance data and export reports via USB interface
Installation	Wall mounting
Platform	Safire Control Center