

CCTV Analógico / HD 4n1 / Cameras


SF-T020CA-5B1-0360

SF-T020CA-5B1-0360

B1 Range: Budget Friendly and Basic Functions

With models ranging from 2MP to 5MP, the B1 range provides an analogue solution at a very competitive price. Models are available with NightColor functionality, offering 24-hour colour viewing. They come with Smart IR (white supplementary light) which will allow colour viewing in case the light gets low enough. With a very affordable price, this range offers simple but very efficient features for the most basic installations, such as 2D DNR technology for noise reduction or DWDR to improve image quality.

- Turret camera 3 in 1 Range B1
- 5 Mpx (2560x1936) , 1/2.5" CMOS
- lens 3.6 | White LED lighting 30 m
- DWDR, HLC, BLC, AGC
- Weatherproof IP67



Technical Specification

Camera	
Image Sensor	1 / 2.5 "CMOS
Resolution	5MP
Image Size	2560 x 1936
Video Output	AHD / TVI /CVI
Audio	1CH built-in MIC
Image System	PAL / NTSC
Electronic Shutter	Auto; 1/50s~1/00000s(P); 1/60s~1/100000s(N)
IR Distance	20 ~30 m
Frame Rate	5MP@20fps /4MP@30fps
Min. Illumination	0 lux with LED ON
Lens	3.6 mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP 67
Functions	
Function Control	OSD (COC Control)
Smart LED	Yes
Digital WDR	Yes
Digital NR	Yes, 2D DNR
Global Exposure	Yes
Central Exposure	Yes
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	No
Contrast	Yes
Sharpness	Yes
Coaxial audio	Yes
Image Setting	Yes

Defect Correction	Auto
Language	Chinese/English
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
Others	
Power Supply	DC12V (± 10%)
Power Consumption	LED OFF : < 1.5 W; LED ON : < 3W
Working Environment	- 30 °C ~ 50 °C, 10 % ~ 90 %□relative humidity□
Dimensions (mm)	□ 94.6 x 82.8
Weight (net)	Approx. 0.39KG