

Video-intercoms / Monitors

# SF-VIDISP08-7WIP-A

## Indoor station

### TFT Monitor touch screen

Monitor range: TFT touch screen video door entry with a clear and sharp image. Aesthetic and quality design. With functions such as bidirectional communication, real-time notifications, remote viewing and opening of the door from the application via P2P cloud, as well as the possibility of recording on a MicroSD card. Integration in both 2-wire and IP environments, even a combination of both. Adaptability to different environments, such as single-family homes, apartment blocks or neighborhood communities.

- Videointercom Monitor
- Communication Standard PoE, WiFi, SIP
- 7" TFT Touch Screen
- Bidirectional audio
- Supports Android Applications | Slot microSD
- Mobile App
- Surface mounting | Color White



## Technical Specification

<b>Operating system</b>	Embedded Android operation system
<b>ROM</b>	2 GB
<b>RAM</b>	8 GB Emmc
<b>CPU</b>	Embedded processor
<b>Screen size</b>	7-inch
<b>Operation method</b>	Capacitive touch screen
<b>Type</b>	Colorful TFT
<b>Resolution</b>	1024 × 600
<b>Lens</b>	/
<b>Resolution</b>	/
<b>FOV</b>	/
<b>WDR</b>	/
<b>Video compression standard</b>	/
<b>Focal length</b>	/
<b>Audio compression standard</b>	G.711 U, G.711 A
<b>Audio input</b>	Built-in omnidirectional microphone
<b>Audio output</b>	Built-in loudspeaker
<b>Audio compression bitrate</b>	64 Kbps
<b>Audio quality</b>	Noise suppression and echo cancellation
<b>Volume adjustment</b>	Adjustable
<b>Event capacity</b>	200
<b>Notice capacity</b>	16
<b>Linked indoor extensions capacity</b>	5
<b>Communication protocol</b>	TCP/IP, SIP, RTSP
<b>Wired network</b>	Support
<b>Wi-Fi standard</b>	Wi-Fi 802.11 b/g/n
<b>Bluetooth version</b>	/
<b>3G/4G standard</b>	/
<b>Zigbee</b>	/
<b>Alarm input</b>	8

<b>Network interface</b>	1 RJ-45 10/100 Mbps self-adaptive
<b>TAMPER</b>	/
<b>RS-485</b>	1
<b>TF card</b>	1
<b>Alarm output</b>	1 relay output, 1 alarm output
<b>Power interface</b>	1
<b>Button</b>	/
<b>Installation</b>	Surface mounting
<b>Indicator</b>	/
	Without package: 419.3 g With package: 694 g
<b>Protective level</b>	/
<b>Working temperature</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Working humidity</b>	10% to 90%
<b>Dimensions</b>	187 mm × 137 mm × 25.7 mm (7.36" × 5.39" × 1.01")
<b>Battery</b>	/
<b>Power supply</b>	IEEE802.3af, standard PoE 12 VDC, 1 A
<b>Application environment</b>	Indoor
<b>Power consumption</b>	≤ 8 W
<b>Language</b>	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Norwegian, Danish