

CCTV Analógico / Cámaras

# UV-UAC-T115-AF28

Uniview



## Características

---

- Uniview
- Cámara Turret Analógica
- 1/2.7" Progressive Scan CMOS
- 5 Megapíxel (2880x1620)
- Lente 2.8 mm
- 0.02 Lux
- IR Alcance 20 m
- IR CUT
- TVI/AHD/CVI/CVBS
- Micrófono integrado- Impermeable IP67

## Especificaciones

<b>Gama</b>	Uniview
<b>Sensor de imagen</b>	1/2.7" Progressive Scan CMOS
<b>Resolución máxima</b>	5MP
<b>Tasa Main Stream</b>	5MP@25fps: 2880x1620; 5MP@20fps: 2592x1944; 5MP@12.5fps: 2592x1944
<b>Tasa Extra Stream</b>	4MP: 2560x1440, 2MP: 1920x1080
<b>Tasa Tercer Stream</b>	1080P: 1920x1080
<b>Lente</b>	2.8 mm
<b>Ángulo de visión (FOV)</b>	110.0° (H), 57.0° (V), 130.0° (D)
<b>Iluminación mínima</b>	0.02 Lux (Color)
<b>Audio</b>	Micrófono Integrado
<b>Alcance Infrarrojos</b>	20 m
<b>Mejoras de imagen</b>	BLC, HLC, DWDR, DAY/NIGHT MODE, 2D. DWDR. SMART IR
<b>Día / Noche</b>	3 Modos (Auto /Día / Noche)
<b>Salida de vídeo</b>	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL, NTSC
<b>Interface</b>	5.5 mm
<b>Temp. funcionamiento</b>	-30° C ~ 60° C
<b>Grado de protección</b>	Impermeable IP67
<b>Alimentación</b>	DC 12 V / 3.3 W
<b>Dimensiones</b>	118mm (?) * 96mm (H)
<b>Peso</b>	183 g