



YBN-R/4IS(WHT)

Base para detectores intrínsecamente seguros.

General

The YBN-R/4IS(WHT) is a WHITE conventional detector mounting base associated with the conventional range of intrinsically safe detectors which is fully compatible with the majority of existing conventional fire alarm control panels.

Installation

The YBN-R/4IS(WHT) is supplied with square cable clamps for secure and reliable cable termination. Note that this base does not provide line continuity during detector removal (head out support). If manual call points are therefore being used, then these should be wired onto the zone first.



Detalles

- Low profile
- Rugged design
- Dedicated cable screen terminal
- Accepts from 1 to 2.5 mm² cables
- Quick connection via square cable clamps
- Electronics free

YBN-R/4IS(WHT)

Base para detectores intrínsecamente seguros.

Especificaciones técnicas

General

Compatibilidad	Aritech, Kilsen & Ziton conventional zone interfaces
Conectividad	2-wire zone

Eléctrico

Especificaciones del cable	1 to 2.5 mm ²
No. de núcleos de cable	2
Terminales	6

Físico

Dimensiones físicas	100 x 8 mm
Peso neto	51 g
Color	Blanco
Tipo de Montaje	Montaje en el techo
Entradas de cable	1
Material (caja)	ABS
Marcado funcional	BASEEFA Rating
Centros de fijación	48 to 74 mm

Medioambiental

Antivandálico	No
Humedad relativa	<95% noncondensing @ 40°C
Entorno	Interior, IS

Regulador

Cumplimiento	CE
Certificación	CENELEC/ATEX

Productos compatibles

Categoría	Referencia	Descripción
Dispositivo de detección	DCD-1E-IS(WHT)	Detector convencional de temperatura intrínsecamente seguro.