

Audiovisuals / Digital Signage

SF-55DS30

Professional Digital Signage Monitors

Professional digital signage monitors

Digital signage is an advertising format based on the broadcasting of digital content such as images, videos, web content, etc. on multiple devices, including monitors. Generally, these monitors are located at the point of sale or in key locations, being able to create, manage, distribute and publish such content.

- Monitor SAFIRE ELED 55" 4K
- Software de cartelería digital local
- Entrada HDMI, USB, RS232, RJ-45
- Ángulo de visión de 178°
- Altavoces integrados



Technical Specification

Information	- Android intelligent commercial display screen equipped with messaging - Compatible with horizontal and vertical screen installation
Installation	Support VESA 300x300mm
Inch	55"
Panel type	VA
Display resolution	3840x2160 (4K)
Brightness	250 cd/m2
Contrast	4000:1
Viewing angle	178° (H) 178° (V)
Response time	6,5 ms
Display scale	16:9
Panel life	>= 30000 h
Colour gamut	>= NTSC 68%
Working time	8/7
CPU	MT9679
RAM	2 GB
ROM	16 GB
OS	Android 14.0
WiFi	2.4 GHz / 5 GHz 802.11a/b/g/n/ac
USB 2.0	x1
USB 3.0	x1
HDMI 2.0	x3
Line OUT	x1 (3.5mm)
RJ45	x1 (100/10 Mbps)
RS232 (DB9)	x1
Input power	110-240 V @ 50 / 60 Hz
Monitor size	1226 (W) x 709,4 (H) x 82 (D) mm
Net weight	6,9 Kg
Speaker	2 x 10 W
Rated power	135 W
Standby power	0.5 W

Work enviroment	Temperature: -10°C - 40°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa
Storage enviroment	Temperature: 20°C - 55°C Humidity: 20% - 80% Atmos: 86 KPa - 106 KPa