1210A

SIMPLEBUS2 POWER SUPPLY UNIT



Power supply unit for audio or audio/video systems with 1 input compatible with all outdoor entrance panels featuring Simplebus 2 technology and 1 output for the connection of devices such as door-entry phones and door entry monitors featuring Simplebus 2 technology. Supplied with line termination terminal art. 1216.

The technical specifications are subject to change without prior notice.

1210A

SIMPLEBUS2 POWER SUPPLY UNIT

MAIN FEATURES	
Supply voltage	230VAC / 50÷60Hz
Output supply voltage	34VDC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	8

GENERAL DATA	
Width (inch) (in)	5.63
Height (inch) (in)	2.44
Depth (inch) (in)	3.54
Type of finishing materials	Plastic
Product color	White
Operating temperature (°F)	32 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75

HARDWARE SPECIFICATIONS	
Product weight (oz) (oz)	81.13

COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes

MOUNTING/INSTALLATION	
Wall-mounted	Yes

ELECTRICAL SPECIFICATIONS	
Maximum current absorption (mA)	350
Maximum power delivered (W)	34

The technical specifications are subject to change without prior notice.