

Product: 70045LV

Speaker Cable LSZH 2x1.5mm², CPR B2ca.

Product Description

Speaker Cable, 2 Conductor 1.5mm² (30 x 0.25mm) Oxygen-Free Bare Copper (High Conductivity), LSZH Insulation, LSZH Jacket, Flexible, CPR Euroclass B2ca.

Technical Specifications

Product Overview

Suitable Applications:	Speaker cable for use in indoor or outdoor applications

Construction Details

Conductor

Size	Stranding	Material
1.5 mm²	Stranded	BC-OFHC - Oxygen-Free Bare Copper (High Conductivity)

Insulation

Material	Nom. Insulation Diameter	Color Code
LSZH - Low Smoke Zero Halogen (Flame Retardant)	2.30 mm (0.0906 in)	Black, Red

Outer Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.80 mm (0.268 in)

Outer Jacket1 Table Notes:	Matte Finish
Overall Cable Diameter (Nominal):	6.80 mm (0.268 in)

Electrical Characteristics

Electricals

Max. Conductor DCR	Nom. Capacitance Cond-to-Cond
13 Ohm/km (4.0 Ohm/1000ft)	110 pF/m (34 pF/ft)

Voltage

Voltage Rating
300 V

Mechanical Characteristics

Temperature

Storage
-30°C to +70°C

Max. Pull Tension:	200 N (45 lbf)

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor - Euroclass B2ca, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance - UL 1581 sec 1200 Black Only
Flammability / Reaction to Fire:	IEC 60332-1-2

CPR Compliance:	CPR Euroclass: B2ca-s1,d1,a1
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3, IEC 61034-2 - Smoke Density Min. Transmittance = 60%

History

Update and Revision:	Revision Number: 0.187 Revision Date: 10-21-2026

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
70045LV.00100	Black	Reel	100 m	8719605163370
70045LV.00250	Black	Reel	250 m	8719605163387
70045LV.00500	Black	Reel	500 m	8719605163363
70045LV.01100	Gray	Reel	100 m	8719605177643
70045LV.01250	Gray	Reel	250 m	8719605177650

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.