Product data sheet

AD88-1000

Cable sensor térmico digital 88º. Recubrimiento PVC. 1.000m.

General

The AD88-1000 is a Digital Linear Heat Detection (LHD) cable with a 88°C (190°F) fixed temperature activation rating. It has a Standard PVC outer sheath making it suitable for internal applications and is supplied in 1000m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' ,'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- cUL/UL 521 approved
- FM approved (Class 3210)
- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas

AD88-1000

Cable sensor térmico digital 88º. Recubrimiento PVC. 1.000m.

Technical specifications

Electrical

Voltaje de funcionamiento	0 to 30VAC, 0 to 42VDC
Operating voltage	0 to 30VAC, 0 to 42VDC
Conductor resistance	~100 ohms/km per leg (30.4 ohms/Kft)
Capacitance	88 to 150pF/m
Inductance	540 to 1050nH/m

Physical

Peso neto	20 kg
Color	Blanco

Environmental

Humedad relativa	0 to 100% noncondensing
Entorno	Interior, Exterior
Ambient temperature (max)	69°C (156°F)
Relative humidity	0% to 100%

Standards & regulation

Certificación	CE, FM, UL

Mechanical

Outside diameter (Nominal)	3.6mm ± 0.12mm
No of cores	2
Colour	White
Weight	20kg

Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 July 2021 - 10:01