Capture by ADI

PRODUCT SPEC SHEET

CAP-27LED3-L

27" BNC FRAMELESS LED MONITOR

24/7/365 Operating Capability



The 27" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colors, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

FEATURES

- 27" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, Audio and Dual Power Cables (EU,UK)
- Two Built-In Speakers
- 36-Month Warranty

- Part #: CAP-27LED3-L
- UPC: 840049312258
- Length: 24.1" (612.1mm)
- Width: 8.6" (218.4mm)
- Height: 17.5" (444.5mm)
- Weight: 7.82 lbs. (3.5kg)
- UL Listed

FC CE UK CA RoHS COMPLIANT c UL us E505978 LISTED SMH7

SELECT SERIES

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

Capture by ADI

FICHE SIGNALÉTIQUE

CAP-27LED3-L

MONITEUR BNC À DEL SANS CADRE DE 27 PO

Capacité de fonctionnement 24/7/365



Le moniteur BNC à DEL sans cadre de 27 po est parfait pour les applications de vidéosurveillance en permanence. Grâce à une résolution HD intégrale et à ses 16,7 millions de couleurs, ce moniteur saura afficher tous les détails avec précision. Les entrées HDMI et VGA et une entrée/sortie BNC accueillir plusieurs appareils et permettre le bouclage BNC. Le moniteur est aussi doté de fonctionnalités de détection automatique de la source et de mise à l'échelle pour une configuration facile.

CARACTÉRISTIQUES

- Dimensions d'achage diagonales de 27 po
- Résolution HD intégrale 1920x1080 p
- Grand angle de vue de 178°
- Détection automatique de la source
- Technologie à faible lumière bleue
- Mise à l'échelle Quick Touch 16:9/4:3
- Entrées BNC, VGA, HDMI et audio
- Comprend des câbles audio, VGA et Câble d'alimentation (EU, UK)
- Deux haut-parleurs intégrés
- Garantie de 36 mois

- N° de pièce : CAP-27LED3-L
- UPC : 840049312258
- Longueur : 24,1 po (612,1 mm)
- Largeur : 8,6 po (218,4 mm)
- Hauteur : 17,5 po (444,5 mm)
- Poids : 7,82 lb (3,5 kg)
- Homologué UL

FC CE UK CA RoHS COMPLIANT c UL us E505978 LISTED SMH7

SÉRIE SELECT

POUR DE PLUS AMPLES RENSEIGNEMENTS, COMMUNIQUEZ AVEC UN REPRÉSENTANT ADI.

Capture by ADI

PRODUCT SPEC SHEET

CAP-27LED3-L

TECHNICAL SPECIFICATIONS	
Model	CAP-27LED3-L
Screen Diagonal Dimension (inches)	27"
Viewable Area W x H	23.5" x 13.2" (596.9mm x 335.2mm)
LED Type	Edge LED
Pixel Pitch (mm)	0.3114mm x 0.3114mm
Screen Maximum Resolution	1920x1080
Display Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Supported Input Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Refresh Rate (hertz)	60Hz
Color Depth (millions)	16.7 million colors
Brightness	250 nits (250 cd/m^2)
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD options: Full/4:3/Over Scan
Horizontal TV Lines	1080
Contrast Ratio	4000:1SCR
Response Time (ms)	5 ms (GTG)
View Angle H/V (degrees)	178° x 178°/CR＞10
Digital Video Inputs	HDMI up to 1920x1080
Analog Video In/Out	VGA up to 1920x1080
Connectors	HDMI x 1 , VGA x 1 , BNC IN x 1 , BNC OUT x 1 , AUDIO OUT x 1
Audio Inputs (stereo)	1 x 3.5mm mini-jack
Speakers (watts)	2 x 2 watts
Stand-by (watts)	＜0.5 watt
Power Consumption (watts)	20 watts typical
Monitor Body Dimensions	24.1" x 1.6" x 14.2" (612.1mm x 40.6mm x 360.6mm)
Dimensions Monitor+Stand	24.1" x 8.6" x 17.5" (612.1mm x 218.4mm x 444.5mm)
Panel Surface	Matte black
Case and Stand Material	Plastic
VESA Mounting Pattern (mm)	100mm x 100mm
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only	7.05 lbs. (3.2kg)
Weight Cabinet+Base Stand	7.82 lbs. (3.5kg)
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10~90%
Accessories Included in the Box	Dual power cable(EU,UK)/VGA cable/Audio cable/IR Remote Stand support/Screws/Base of stand/User manuals
Mounting Screw Size (mm)	M4-L8 mm/4pcs
Certifications	CE/FCC/RoHS/HDMI/UL/WEEE/REACH/UKCA
Warranty	36 Months

SELECT SERIES

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.