

DL 50

E-NR: 6309221

Door loop with metal housing

The DL 50 door loop with metal flexi-tube and housing for enhanced security is used to simplify and protect transmission of signals with a cable from windows and doors to the frame.

It comes complete with 2 junction boxes in metal with opening and pry off protection and a stainless steel flexi-tube. The stainless steel flexi-tube is available in 2 lengths – 400 mm and 600 mm.

The cable is protected against the sharp edges of the flexi-tube at each end with a plastic conduit that allows a maximum cable diameter of 4 mm.

The flexi-tube is secured with locking grooves in the base of the box for a safe connection. Each junction box has a 10-screw terminal with wire protection, 2 of which are specified for the tamper switch.

If other lengths of the stainless steel flexi-tube are required the MC T2, MC T4 or MC T7 are suitable.

TECHNICAL DETAILS

Length (m)	0,4,0,6
Dimensions (L x W x H) mm	86 x 41 x 23
Outer diameter mm	8
Inner diameter mm	6
Length (mm)	DL 50-40 – 400 mm, DL 50-60 – 600 mm
Product type	Connection accessories
Max cable diameter (mm)	4
Environment	Indoor

Frame transfer	Cable protection
Product line	Alarmtech
Product feature	Surface-mounted

ORDER INFORMATION

Model	E-NR	Description
DL 50-40	6309221	Door loop with metal housing, 400 mm, stainless steel
DL 50-60	6309222	Door loop with metal housing, 600 mm, stainless steel