Honeywell Home

SMPG-UK

Smart Plug

APPLICATION

The SMPG-UK offers home automation capability with easy to use smart devices in addition to a Honeywell Home security wireless intruder systems.

The SMPG-UK can locally and remotely operate any device connected to them: lights, radio, heater, etc. and support high loads up to 3680W.

When the user is at home, they can easily operate the Smart Plug(s) with a keyfob or a keypad. The Smart Plug (s) can also be controlled remotely using the Total Connect 2.0E web application.

Using Total Connect 2.0E allows the user to see the consumption of the devices connected to the Smart Plug(s).

The SMPG-UK can also be used in installations with scenarios which will automatically switch them ON or OFF depending on what happens at home.

For example switching on the smart plug when the system is disarmed to switch on a light, or switching on the smart plug when there is an alarm to alert with an external device.



SPECIAL FEATURES

- Remote ON/OFF with a keyfob, keypad or remotely(1)
- Built-in button to switch the smart plug. ON or OFF locally (with LED status)
- Scenarios to fit real life usage: turn on lights when an alarm is triggered, turn off the radio when the home owner is back
- Instantaneous power consumption of the device (1) connected to the Smart Plug
- Web server API for integration in a customised User Interface
- Up to 6 Smart Plugs per installation
- Supports high loads up to 3680W(2)

(1) When used with Total Connect 2.0E and Cloud services
(2) Depending on the model (see table on the back)

SMPG-UK - Smart Plug

SPECIFICATIONS	
INPUT / OUTPUT VOLTAGE	230VAC, 50Hz
CONSUMPTION	< 0.8W (standby) < 1.8W (active)
MAXIMUM LOAD (RESISTIVE)	13A / 2990W (SMPG-UK) 16A / 3680W (SMPG-EU)
MEASURING RANGE	190V to 276V 20mA to 16A 4W to 3680W (resolution 1W)
RADIO RANGE	>50m on site (2000m in open field)
BUTTON / LED	For local command and signalling
SUPERVISION	Yes
DIMENSION (H X W X D)	115 x 64 x 64 mm
OPERATING TEMPERATURE	5°C to +45°C
STORAGE TEMPERATURE	-20°C to +70°C
RELATIVE HUMIDITY	5% to 95% (non condensing)

ORDERING INFORMATION	
SMPG-UK	Smart Plug with UK Plug

TOTAL CONNECT 2.0E SCREENSHOTS



ONLY FRENCH SCREENSHOTS IN INDESIGN SOURCE FILES

Resideo Technologies, Inc.
200 Berkshire Place,
Winnersh, Berkshire,
RG41 5RD

© 2021 Ademco 1 Ltd. All rights reserved. The Honeywell Home trademark is used under license from Honeywell International Inc. These products are manufactured by Ademco 1 Ltd and its affiliates. This document contains proprietary information of Ademco 1 Ltd and its affiliated companies and is protected by copyright and other international laws. Reproduction or improper use without specific written authorization of Ademco 1 Ltd is strictly forbidden.

resideo