

SecuriSmoke ASD 531/532/533/535

Product Catalogue 2023

Sampling point with heating



HEAT 3.0 ABS	red	**50-0500451-02-01**
HEAT 3.5 ABS	blue	**50-0500452-02-01**
HEAT 4.0 ABS	green	**50-0500453-02-01**
HEAT 4.5 ABS	black	**50-0500454-02-01**
HEAT 5.0 ABS	brown	**50-0500455-02-01**

To install the aspirating pipe in deep-freeze rooms to prevent the freezing of the aspirating holes. HEAT X.X is the relevant diameter for ASD PipeFlow-calculations (3.0/3.5/4.0/4.5/5.0mm)

Dimensions (Ø):	25 mm

Hole Diameter	
5,7 mm	HEAT 3.0 ABS
6,1 mm	HEAT 3.5 ABS
6,3 mm	HEAT 4.0 ABS
6,7 mm	HEAT 4.5 ABS
7,1 mm	HEAT 5.0 ABS

Heat Resistor



Heat Resistor **11-2300079-01-01**

Replacement for the sampling point with heating HEAT X.X ABS.

- Resistor: 220 Ω

Silicon litz wire



SLW 0.5 wt	white	**50-0500483-01-01**
SLW 0.5 bk	black	**50-0500482-01-01**

Silicon litz wire 0.5mm² to connect the heating resistors in the heating nozzles HEAT X.X ABS.
Delivery unit: 100 m

Wiring connection unit



WCU 535 PC **11-2300046-01-01**

For the introduction of the supply of sampling points with heating into the aspirating tube, with internal clamps.
For more details, please see the guidelines for deep freeze-warehouses.

- Pipe connection Ø 25 mm

Weight:	317 g
Dimensions (HxWxD):	150 × 107 × 85 mm
Material:	PC
Color:	light grey (RAL 7035)