




10-Port Industrial Gigabit PoE+ DIN-Rail Switch

TI-PG102 (v1.3R)

- 8 x Gigabit PoE+ ports
- 2 x 1000Base TX/FX RJ-45/SFP shared ports
- 240 W PoE power budget
- 20 Gbps switching capacity
- Hardened IP30 rated metal switch
- Includes DIN-rail and wall mounts
- Operating temperature range of -40° – 75°C (-40° – 167°F)
- Dual redundant power inputs with overload current protection
- Alarm output triggered by power failure
- Power supply sold separately (models: TI-S24048 / 48VDC3000)

TRENDnet's 10-Port Industrial Gigabit PoE+ DIN-Rail Switch, model TI-PG102, has eight gigabit PoE+ ports with a 240 W PoE power budget, plus two gigabit RJ-45 / SFP shared ports. Users are able to connect eight PoE+ devices to the switch, while still providing two gigabit ports for additional network connections. The switch is equipped with an IP30 rated metal enclosure, designed to withstand a high degree of vibration and shock, while operating within a wide temperature range of -40° – 75°C (-40° – 167°F) for industrial environments.







PoE Power

A 240 W PoE+ power budget supplies up to eight Power over Ethernet devices with PoE+ power.


Fault Tolerance

Features dual redundant power inputs with output alarm relay.

Industrial Hardened Design

Equipped with a rugged IP30 rated housing, designed to withstand a high degree of vibration, shock, and operate within a wide temperature range of -40 – 75°C (-40 – 167°F).

Networking Solution



1. AC power port
2. Terminal slot for DC power
3. Grounding point
4. Shared Gigabit RJ-45 ports
5. LED indicators
6. Gigabit PoE+ ports
7. Shared Gigabit SFP slots
8. Wall mount kit
9. Screws
10. Din-rail mount
11. Terminal block

Full PoE+ Power Budget
Supplies up to 30 W of PoE / PoE+ power per port with a 240 W PoE power budget

Network Ports
8 Gigabit PoE+ ports plus 2 1000Base TX/FX RJ-45/ SFP shared ports

DIN-Rail / Wall Mounts
IP30 rated metal enclosure with included DIN-rail and wall mount hardware

Switching Capacity
20 Gbps switching capacity

Redundant Power
Dual redundant power inputs with overload current protection (power supply sold separately models: TI-S24048 / 48VDC3000)

Alarm Relay
Alarm relay triggered by power failure of primary and / or redundant power

Jumbo Frame
Sends larger packets, or Jumbo Frames (up to 10 KB), for increased performance

Extreme Temperatures
Industrial switch is rated for an operating temperature range of -40 – 75°C (-40 – 167°F)

Shock and Vibration Resistant
Rated for shock (EN 60068-2-27), freefall (EN 60068-2-32), and vibration (EN 60068-2-6)

Grounding Point
Grounding point protects equipment from external electrical surges

Specifications

Standards
- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3z
- IEEE 802.3x
- IEEE 802.3af
- IEEE 802.3at

Device Interface
- 8 x Gigabit PoE+ ports
- 2 x 1000Base-TX Ethernet ports
- 2 x Shared 1000Base-FX SFP slots
- 6-pin removable terminal block
- LED indicators
- DIN-Rail mount
- Wall mount
- Grounding point

Data Transfer Rate
- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

Performance
- Data RAM Buffer: 256 KB
- Switching Fabric: 20 Gbps
- MAC Address Table: 16 K entries
- Forwarding rate: 14.8 Mpps (64-byte packet size)

AC Power
- Input: 100 – 240V AC, 50/60Hz, 2A
- Compatible power adapter: 48VDC3000 (sold separately)
- Output: 48V DC, 3.34A 160W max.

Special Features
- Hardened components rated for extreme temperatures
- Dual redundant power inputs
- Auto-Negotiation
- Auto store and forward architecture
- Automatic address learning and address aging
- ESD 6 KV protection

Power
- Input: 48 - 56 V DC
- Compatible power supply: TI-S24048 (sold separately)
- Max. consumption: 5.67W (no PoE)

PoE
- Per port up to 30 W
- PoE budget: 240W@56V DC

Terminal Block
- Redundant power inputs, alarm relay contact, 6 pin
- Wire range: 0.34 mm^2 to 2.5 mm^2
- Solid wire (AWG): 12-24 / 14-22
- Stranded wire (AWG): 12-24 / 14-22
- Torque: 5 lb. – In / 0.5 Nm / 0.56 Nm
- Wire strip length: 7-8 mm

Alarm Relay Contact
- Relay outputs with current carrying capacity of 1 A, 24 V DC
- Open circuit mode when two power sources are connected
- Short circuit mode when only one power source is connected

MTBF
- 510,400 hours

Housing
- IP30 metal case
- DIN-rail mount
- Wall mount
- Grounding point
- ESD 6 KV protection

Operating Temperature
- - 40 to 75 °C (-40 to 167 °F)

Operating Humidity
- Max. 95 % non-condensing

Dimensions
- 155 x 120 x 48 mm (6.1 x 4.7 x 1.9 in.)

Weight
- 445 g (1 lb)

Certifications
- CE
- FCC
- Shock (EN 60068-2-27)
- Freefall (EN 60068-2-32)
- Vibration (EN 60068-2-6)

Warranty
- Limited Lifetime Warranty*

Package Contents
- TI-PG102
- Quick Installation Guide
- Removable terminal block
- DIN-rail and wall mount kit

*TRENDnet offers a limited lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • sales@trendnet.com • www.TRENDnet.com

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.

Updated: 3/5/2026