CE EN 54-24

PREVIDIA | ULTRA

DEL-W 165/6 PP

6.5” 6W CEILING MOUNT PENDANT LOUDSPEAKER

The DEL-W 165/6 PP pendant loudspeaker for voice evacuation systems is a 6.5” loudspeaker designed to be installed in structures characterized by high ceilings, such as commercial buildings, warehouses, factory production areas, airports and railway stations where a sound source as close to the listener's ear is required.
The device, made in steel, is powder coated to prevent cracking and discoloration of the product and is supplied with a 5m long cable that can be adjusted according to installation needs. In addition, at the end of the cable there is a connection casing containing a ceramic terminal block and a thermal fuse.
EN54-24 certified.



TECHNICAL SPECIFICATIONS

Main features

- 6.5” speaker
- Suitable for 70V or 100V lines
- Equipped with internal transformer for adapting the power parameters
- Ceiling mount
- Internal selector to adjust the output power to 6 / 3 / 1.5 / 0.75 W
- White colour
- Ceramic connection terminal
- Thermal protection fuse included
- EN54-24 certified

Electrical specifications

Power (PHC)	6 / 3 / 1.5 / 0.75 W (internal selector)
SPL (Sound Pressure Level)	
Frequency response	300 Hz – 16.500 KHz (-10 dB)
Operating voltage	70 – 100 Vrms

Mechanical specifications

IP protection grade (according to EN54-24 / IP Rating)	32C
Enclosure material	Steel
Dimensions	Ø 210 x 75 mm
Weight	1.29 Kg
Colour	White RAL 9010
Mounting type	ceiling mount

ORDER CODE

DEL-W 165/6 PP 6.5” 6W ceiling mount pendant loudspeaker

Centobuchi, via Dei Lavoratori 10
63076, Monteprandone (AP), ITALY
Tel. +39 0735 705007 _ Fax +39 0735 704912

Inim distributor’s stamp
and signature

DCSTINE0DELW1656PP-100-20230127