DHI-VTO2003F

2-wire Hybrid Villa Door Station



- Aluminum alloy front panel.
- Offers video intercom which communicates through half-duplex.
- Auto IR illumination.
- Video messages can be left for unanswered calls. (SD card is required for VTH.)
- Features nameplate and DWDR.
- Supports local lock and second lock.
- Offers anti-tampering alarm.
- IP65 and IK07 rated.




Technical Specification

System	
Main Processor	Embedded Processor
Button Type	Mechanical
Basic	
Camera	1/2.8" 2 MP CMOS HDR Camera
Field of View	H: 110°; V: 60°
WDR	DWDR
Noise Reduction	3D NR
Video Resolution	P: 960 (H) × 576 (V) N: 960 (H) × 480 (V)
Video Frame Rate	P: 25 fps N: 30 fps
Light Compensation	Auto IR
Day/Night	Auto(ICR)/Color/B/W
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio (half–duplex)
Function	
Unlock Mode	Remote unlock
Leave Videos	Yes (SD card inserted in VTH is needed)
Performance	
Casing Material	Aluminum Alloy
Port	
RS-485	1
Alarm Output	1
Power Output	1(12 V/200 mA)
Exit Button	1
Door Status Detection	1
Lock Control	1
Alarm	
Tamper Alarm	Yes
General	
Appearance Color	Silver
Power Supply	2- wire controller
Power Adapter	Optional
Installation	Flush Mount;Surface Mount
Certifications	CE; FCC
Accessory	Sold separately: surface box, rain cover, flush box, 2-wire controller
Product Dimensions	130 mm × 96 mm × 28.5 mm (5.12" × 3.78" × 1.12")
Protection	IP65 IK07
Operating Temperature	–40 °C to +60°C (–40 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Altitude	0 m–3000 m (0 ft – 9842.52 ft)
Power Consumption	≤ 1.5 W (standby), ≤ 10 W (working)
Gross Weight	0.326 kg (0.72 lb)
Storage Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Storage Humidity	95% (RH), non-condensing


Ordering Information

Type	Model	Description
VTO	DHI-VTO2003F	2-wire Hybrid Villa Door Station
Accessories	VTM115	Surface Mounted Box[sold separately]
	VTM114	Flush Mounted Box[sold separately]
	VTM05R	Surface Mounted Box With Rain Cove[sold separately]
	VTNC1003C	2-wire Controller[sold separately]


Dimensions (mm[inch])



Installation



Application



Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice.
The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.