Stratos Micra 25



LPCB
Cert. No. 1199d

Micra 25 maintains all the distinctive features of Stratos (ClassiFire® Perceptive Artificial Intelligence Dual TechnologyLDD 3D3). Micra 25 is the most cost-efficient way of creating a laser-based aspirating system. In fact, it is capable of drawing air from the protected area through a sampling pipe of up to 50m long. Micra 25 is suitable for installation in small applications or rooms which require individual incipient fire reporting. This device is equipped with an RS485 which allows the connection of several devices in a network.
Supplied complete with PIPECAD software.

Technical specifications

- Supply voltage: 21.6V - 26.4V DC
- Current consumption: 250mA @ 24V DC
- Dimensions: 140W x 200H x 85D
- Weight: 1.7kg
- Operating temperature range: -10 to +38°C (UL268) /-10 to + 60°C (CEA4022)
- Operating humidity range: 0 - 90% non-condensing
- Detection range: (%Obs/m) 0.0015% to 25%
- Maximum smoke opacity: 0.0015%
- Detection technology: laser light scattering mass detection and particle evaluation
- Sensitivity: 0.003µ to 10µ.
- Dust Discrimination: 3D3 Laser Dust Discrimination (LDD).
- Maximum sampling pipe length in a high-airflow environment: 25m
- Maximum sampling pipe length in a static-air environment: 50m
- Sampling pipe diameter: 3/4" (27mm O/D)
- Sampling holes: 10
- Alarm levels: 4 (Aux, Pre-alarm, Fire 1 and Fire 2)
- Laser sampling chamber life: 10 years
- Laser system life (MTTF): 1000 years
- Up/Download serial port: RS232/RS485
- RS485 Network data bus
- Maximum BUS length: 1.2 km
- Cabinet rating: IP50

Stratos Micra 100



LPCB
Cert. No. 1199d

Micra 100 is suitable for small to medium applications. It is capable of drawing air from the protected area through two sampling pipes for a total length of 100m.
Supplied complete with PIPECAD software.

Technical specifications

- Supply voltage: 21.6V - 26.4V DC
- Current consumption: 400mA @ 24V DC
- Dimensions: 300W x 220H x 85D
- Weight: 3.8kg
- Operating temperature range: -10 to +38°C (UL268) /-10 to + 60°C (CEA4022)
- Operating humidity range: 0 - 90% non-condensing
- Detection range: (%Obs/m) 0.0015% to 25%
- Maximum smoke opacity: 0.0015% obscuration per meter
- Detection technology: laser light scattering mass detection and particle evaluation
- Sensitivity: 0.003µ to 10µ
- Dust Discrimination: 3D3 Laser Dust Discrimination (LDD)
- Maximum sampling pipe length in a high-airflow environment: 50mt
- Maximum sampling pipe length in a static-air environment: 100mt
- Sampling pipe diameter: 3/4" (27mm O/D)
- Sampling holes: 25 x pipe
- Alarm levels: 4 (Aux, Pre-alarm, Fire 1 and Fire 2)
- Laser sampling chamber life: 10 years
- Laser system life (MTTF): 1000 years
- Up/Download serial port: RS232/RS485
- Network data bus: RS485
- Maximum BUS length: 1.2 km
- Cabinet rating: IP50