KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



The kit includes: three Mini series door-entry phones art. 2702W, a transformer art. 1200, an Extra series external unit designed for 2/4 call buttons art. ET5100, 4 single buttons for Extra entrance panel art. ET9211. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the corresponding accessories supplied with the kit.

AWARDS

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

PRODUCTS IN THE KIT



ET5100 **EXTRA 4+N ENTRANCE PANEL PREPARED FOR 2/4 BUTTONS**

Extra series audio entrance panel with stainless steel cover and nameplate backlighting. To be completed with single button art. ET9211 (pack of 4 units) to offer 4 call buttons, or with double-height button art. ET9210 (pack of 2 units) to offer 2 call buttons. The entrance panel can be surface-mounted or flush-mounted using the relevant accessories supplied. Traditional 4 + N wiring system. Dimensions (W x H x D): 95x165x6.5 mm (flush) - 25 mm (surface).

GENERAL DATA	
Type	Monoblock
Width (mm)	95
Height (mm)	135
Depth (mm)	25
Flush-mounted	Yes
Wall-mounted	Yes

COMPATIBLE SYSTEMS	
Traditional	Yes

HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating (with product installed)	IP54
IK vandal-resistance rating (with product installed)	IK07
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95

The technical specifications are subject to change without prior notice.

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

ENVIRONMENTAL AND COMPLIANCE FEATURES

Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

The technical specifications are subject to change without prior notice.

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



2702W **2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL**

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Dimensions: 105x191x28 mm

GENERAL DATA	
Width (mm)	105
Height (mm)	190
Depth (mm)	28
Product weight (g)	260
Product color	White
Type of finishing materials	Plastic
Wall-mounted	Yes
Desk base-mounted	Yes

COMPATIBLE SYSTEMS	
Traditional system	Yes

AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
Loudspeaker	0.50mm, 0.5W

ELECTRICAL CHARACTERISTICS	
Supply voltage	15÷16VDC
Absorption in stand-by (W)	3
Maximum absorption (W)	6

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release, Silent (Privacy)

The technical specifications are subject to change without prior notice.

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

HARDWARE FEATURES	
Clamps	S 2 3 4 P1 P2
Total buttons (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating (with product installed)	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	I (B1)
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES	
Door opener	Yes
Silent mode (Privacy)	Yes
Ringtone volume control	Yes
Electronic bell	Yes

The technical specifications are subject to change without prior notice.

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



1200 **TRANSFORMER 10VA 0-230V/0-12V**

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use.Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230 VAC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9

GENERAL DATA	
Width (mm)	53
Height (mm)	95
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40

COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Semplified system	Yes

ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15

The technical specifications are subject to change without prior notice.

KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

ACCESSORIES



ET9150 FLUSH-MOUNTED BOX FOR EXTRA ENTRANCE PANEL KIT

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm



ET9160 WALL BRACKET FOR EXTRA ENTRANCE PANEL KIT

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm



ET9211 4 SINGLE BUTTONS FOR EXTRA ENTRANCE PANEL

Single buttons to complete the Extra series entrance panel with traditional wiring art. ET5100 and Extra series push-butoon module art. ET5200. Pack of 4 pcs.



1229 EXTENSION SOUNDER

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfacemounted or on civil series 503 box. Dimensions: 110X75X29 mm.

The technical specifications are subject to change without prior notice.