Visonic
From Tyco Security Products

KP-250 PG2

Two-way Keypad that Communicates with PowerMaster Panels



with PowerG Technology

Features that Make a Difference:

- Supports user and installer menus
- Enables a complete view and control of the system
- Designed to work with all PowerMaster panels, including new PowerMaster-33 G2 for residential and SME markets
- Integrated sounder
- Sleek design; wall-mounted or desktop
- Provides user with feedback on commands
- Easy use by keypad, proximity tags or RFID cards
- Partition support
- Provides audible and visual entry/exit warnings
- Extended range eliminates the need for repeaters
- Superb value for price

KP-250 PG2 is a stylish and easy to use two-way wireless user interface for PowerMaster systems. It is an ideal solution for users in both residential and small business premises.

Decorative proximity tags enable users to arm/disarm the system, initiate fire and panic alarms and review system status. Allows installers to maximize system security by installing the panel in a hidden location.

Specifications:

Communication protocol	PowerG
Frequency band (MHz)	USA: 912-918 Europe and rest of world: 433-434, 868-869
Battery type	4AA, 3V, Alkaline
Battery life	Up to 3 years (with typical use)
Power source (optional)	5-12VDC
Operating temperatures:	0˚C to 55˚C (32˚F to 131˚F)
Dimensions	150 x 100 x 20mm (5.9 x 3.9 x 0.8in)
Weight (including battery and bracket)	379g (13oz)
Compliance	Europe: EN301489, EN60950, EN50131-1, EN50131-3 USA: CFR 47 part 15

www.visonic.com

Contact Visonic for further information:
Email: info@visonic.com

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.
© 2014 Tyco Security Products Ltd. All rights reserved. KP-250 PG2 DATA SHEET ENG C-801141 (Rev.00)