ARGUS SECURITY
intelligent fire solutions

PRODUCT DATASHEET

SGCP200

WIRELESS SAGITTARIUS MANUAL CALL POINT


The SGCP200 Manual Call Point (MCP) is a fully intelligent device which is compatible with all Argus Translator and Expander Modules. The unit has a resettable plastic element, which displays a drop down warning flag when operated. A key is supplied with the MCP for reset and case opening. The product is powered by two batteries with a typical life of 10 years and with same form factor, simplifying stock management. The Manual Call Point can be fitted with an optional transparent cover for protection against accidental operation or with a weatherproof enclosure for use outdoors or in hostile environments.



KEY FEATURES

- High reliability
- Bi-directional wireless communication
- 3rd party approval to EN54-11 & EN54-25
- 10 year battery life
- Standard low cost lithium battery technology
- Resettable element
- Self optimising wireless frequency & amplitude algorithms
- 5 year product warranty

TECHNICAL INFORMATION



TECHNICAL SPECIFICATION

Operating frequency range	868 – 870 MHz
Max radiated power	14dBm (25mW)
Radio signal modulation type	FSK
Operating frequency channels	7
Communication range with the Translator or Expander Module	⩽ 150 m (in open space)
IP rating	42
Dimensions	88mm x 87mm x 61mm
Weight (without batteries)	160 g
Batteries	2 x CR123A (3 V & 1.2 Ah)
Batteries lifespan (typical)	10 years
Operating Temperature	-10°C to +55°C
Max humidity (non condensing)	95% RH

STANDARDS & APPROVALS

- EN54-11: Manual Call Points
- EN54-25: Components using radio links and system requirements

CE 2831

LPCB 928p/02

ARGUS SECURITY SRL Via del Canneto, 14 | 34015 Muggia | Trieste - ITALY

ACCESSORIES

ALCI

PROTECTIVE CALL POINT COVER



The ALCI Protective Call Point Cover is an aesthetically pleasing low cost clear cover.
Easily fitted to Argus Call Points, it dramatically reduces both misuse and the risk of accidental activation making it ideal for sports halls, manufacturing and processing facilities, and other high traffic areas.
In addition, the protective Call Point Cover ensures that two positive actions are required to activate the Call Point, making it suitable for territories where dual-activation is mandatory.