TVT

Secure The World With You

CAMERA

TD-7583AE1

8MP HD Analog IR Dome Camera



-
- AHD / TVI / CVI standard and lossless video output
- Up to 1700 TVL resolution
- CMOS progressive scan, perfectly capture the moving object
- Support OSD menu
- High speed, long distance and real time transmission
- Auto color to B / W at low illumination
- Support ICR switch, true day / night
- Support noise reduction function
- 20 ~ 30m IR night view distance
- IP67 & IK 10
- Support COC
- Support 960H CVBS output



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Fax: +86-755-33104777


TD-7583AE1

8MP HD Analog IR Dome Camera

SPECIFICATIONS

Model / Specifications	TD-7583AE1
Camera	
Image Sensor	1 / 2.5 "CMOS
Resolution	8MP
Image Size	3840x2160
Video Output	AHD / TVI /CVI /CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto
IR Distance	20 ~ 30 m
Frame Rate	15fps
Min. Illumination	
Lens	2.8-12 mm, motorized zoom lens
Lens Mount	D14
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP 67 & IK10
Functions	
Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	No
3D NR	Yes
AGC	No
Auto White Balance	Yes
BLC	Yes
Defog	No
LSC	No
Saturation	Yes
Sharpness	Yes
Contrast	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto
Language	11 languages
Angle Adjustment	Pan: 0°~345°; Tilt: 0°~77°; Rotation: 0°~345°
Others	
Power Supply	DC12V (± 10%)
Power Consumption	IR OFF : < 2W; IR ON : < 5 W
Working Environment	- 30 °C ~ 50 °C, 10 % ~ 90 % (relative humidity)
Dimensions (mm)	Φ 141 x 100.2
Weight (net)	Approx. 0.83KG

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-7583AE1(D/AZ/SW/AR2)	Motorized zoom lens

*All pictures and specifications are for reference only and are subject to change without prior notice.